


MDPX-2734CH

Passive MMIC 0 - 60 GHz High Frequency Diplexer

DEVICE OVERVIEW

General Description

The MDPX-2734 is a broadband passive MMIC diplexer, a combination high pass and low pass filter, capable of multiplexing low frequency DC to 27GHz and high frequency 34 to 60GHz signals. Passive GaAs MMIC technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication tolerances allow for less unit to unit variation than traditional filter technologies. The MDPX-2734 is available as a wire bondable chip. Low unit to unit variation allow for accurate simulations using the provided S3P file taken from measured production units.




Features

- 30GHz Crossover Point
- Low <1dB typical Insertion Loss in Pass band
- High Stop Band Suppression
- RoHS Compliant

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MDPX-2734CH	Passive MMIC 0 - 60 GHz High Frequency Diplexer	CH	REACH RoHS	Released	EAR99

Table Of Contents


- **Device Overview**
 - General Description
 - Features
 - Applications
 - Functional Block Diagram
- **Port Configuration and Functions**
 - Port Diagram
 - Port Functions
- **Revision History**
- **Specifications**
 - Absolute Maximum Ratings
 - Package Information
 - Electrical Specifications
 - Typical Performance Plots
- **Die Mounting Recommendations**
 - Mounting and Bounding Recommendations
- **Mechanical Data**
 - Outline Drawing
- **Notes**

Revision History





Revision Code	Revision Date	Comment
-	2017-02-01	Datasheet initial Release
A	2019-05-01	Added more Insertion Loss charts
B	2023-12-19	Updated dimensions on outline drawing.

Port Configuration and Functions

Port Diagram



Port Functions

Port	Function	Description	Equivalent Circuit for Package
GND	Ground	CH package ground path is provided through the substrate and ground bond pads.	
Pad 1	Low Pass Filter	Pad 1 is DC short to Pad 3 and open to Pad 2.	
Pad 2	High Pass Filter	Pad 2 is DC open to Pad 1 and Pad 3.	
Pad 3	Common/Input	Pad 3 is DC short to Pad 1 and open to Pad 2.	

Specifications

Absolute Maximum Ratings

Parameter	Maximum Rating	Unit
Maximum Storage Temperature	125	°C
Maximum Survivable Operating Temperature	125	°C
Minimum Storage Temperature	-65	°C
Minimum Survivable Operating Temperature	-65	°C
RF Power Handling	30	dBm
Spec Guaranteed Operating Temperature	25	°C

Package Information

Parameter	Details	Rating
Dimensions	-	2.28 x 1.25 mm

Electrical Specifications








Specifications guaranteed +25°C for chip (CH) package, measured in a 50Ω system.

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
30 dBc Low Pass Rejection Point	DC to 17 GHz	0	17	27	45	-	dB
Common Port Return Loss	34 to 60 GHz	34	60	10	16	-	dB
Common Port Return Loss	DC to 27 GHz	0	27	10	21	-	dB
High Pass Filter, Pass Band Insertion Loss	34 to 60 GHz	34	60	-	0.9	-	dB
High Pass Filter, Pass Band Return Loss	34 to 60 GHz	34	60	10	15	-	dB
Impedance	-	-	-	-	50	-	Ω
Isolation	16 to 27 GHz	16	27	-	20	-	dB
Isolation	34 to 42 GHz	34	42	-	17	-	dB
Isolation	42 to 60 GHz	42	60	26	33	-	GHz
Isolation	DC to 16 GHz	0	16	25	38	-	dB
Low Pass Filter, Pass Band Insertion Loss	DC to 27 GHz	0	27	-	0.5	-	dB
Low Pass Filter, Pass Band Return Loss	DC to 27 GHz	0	27	10	23	-	dB
Low Pass Filter, Stop Band Rejection	43 to 60 GHz	43	60	27	33	-	dB
High Frequency Passband	-	-	-	34	-	60	GHz
Low Frequency Passband	-	-	-	0	-	27	GHz

MDPX-2734CH

Passive MMIC 0 - 60 GHz High Frequency Diplexer

Typical Performance Plots



Die Mounting Recommendations

Mounting and Bonding Recommendations

Marki MMICs should be attached directly to a ground plane with conductive epoxy. The ground plane electrical impedance should be as low as practically possible. This will prevent resonances and permit the best possible electrical performance. Datasheet performance is only guaranteed in an environment with a low electrical impedance ground.

Mounting - To epoxy the chip, apply a minimum amount of conductive epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip. Cure epoxy according to manufacturer instructions.

Wire Bonding- Ball or wedge bond with 0.025 mm (1 mil) diameter pure gold wire. Thermosonic wirebonding with a nominal stage temperature of 150 °C and a ball bonding force of 40 to 50 grams or wedge bonding force of 18 to 22 grams is recommended. Use the minimum level of ultrasonic energy to achieve reliable wirebonds. Wirebonds should be started on the chip and terminated on the package or substrate. All bonds should be as short as possible <0.31 mm (12 mils).

Circuit Considerations– 50 Ω transmission lines should be used for all high frequency connections in and out of the chip. Wirebonds should be kept as short as possible, with multiple wirebonds recommended for higher frequency connections to reduce parasitic inductance. In circumstances where the chip more than .001" thinner than the substrate, a heat spreading spacer tab is optional to further reduce bondwire length and parasitic inductance.

MDPX-2734CH

Passive MMIC 0 - 60 GHz High Frequency Diplexer


Handling Precautions

General Handling: Chips should be handled with a vacuum collet when possible, or with sharp tweezers using well trained personnel. The surface of the chip is fragile and should not be contacted if possible.

Static Sensitivity: GaAs MMIC devices are subject to static discharge, and should be handled, assembled, tested, and transported only in static protected environments.

Cleaning and Storage: Do not attempt to clean the chip with a liquid cleaning system or expose the bare chips to liquid. Once the ESD sensitive bags the chips are stored in are opened, chips should be stored in a dry nitrogen atmosphere.

Bonding Diagram




MDPX-2734CH

Passive MMIC 0 - 60 GHz High Frequency Diplexer

Mechanical Data

Outline Drawing

Download : [Outline 2D Drawing](#)



Notes:

- CH substrate is .004 Thick GaAs.
- I/O traces and ground plane finish is 2 microns Au.

Notes

DATA SHEET NOTES:

1. Measured typical data available for chip only.
2. Group delay calculated using wrapped phase response.
3. Specifications are subject to change without notice. Contact Marki Microwave for the most recent specifications and data sheets.
4. Catalog circuits are continually improved. Configuration control requires custom model numbers and specifications.

Note: Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

DISCLAIMER

MARKI MICROWAVE, INC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, Inc. All other trademarks used are the property of their respective owners.

© 2017, 2019, 2023, Marki Microwave, Inc