Sales: 408-778-9952 | General: 408-778-4200 | Fax: 408-778-4300
Sales & Customer Support: sales@markimicrowave.com
Tech Support: support@markimicrowave.com

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

DEVICE OVERVIEW

General Description

The MFLP-00045GSM2 surface-mount lowpass filter is an ideal solution for extremely small form factor, high rejection filtering. The MFLP-00045GSM2 features a 4.9 GHz 3 dBc cutoff and 25 dB passband return loss. Its advanced glass substrate technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication ensures tighter unit-to-unit consistency than legacy filter technologies, supporting accurate simulation with the provided S2P data. The MFLP-00045GSM2 is offered in a 4.27 × 4.00 mm package.

Download s-parameters here

Features

- Low Passband Insertion Loss with Fast Roll-off
- 25 dB Return Loss
- High Stop Band Suppression

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MFLP-00045GSM2	Passive Glass 4.9 GHz Surface Mount Lowpass Filter	GSM2	RoHS REACH	Released	EAR99
EVB-MFLP-00045G	Evaluation Board, Passive Glass MMIC 4.9GHz Lowpass Filter	EVB	REACH RoHS	Released	EAR99

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Table Of Contents

- **Device Overview**
  - General Description
  - Features
  - Applications
  - Functional Block Diagram
- **Port Configuration and Functions**
  - Port Functions
- **Revision History**
- **Specifications**
  - Absolute Maximum Ratings
  - Package Information
  - Electrical Specifications
  - Typical Performance Plot
  - Performance Over Temperature
- **Mechanical Data**
  - Outline Drawing
- **Footprint Image**
- **Evaluation Board**
  - Evaluation Board Outline Drawing

Revision History

Revision Code	Revision Date	Comment
-	2025-12-10	Initial Release

Port Configuration and Functions

Port Functions

Port	Function	Description	DC Equivalent Circuit
Pin 1	RF Input	Pin 1 is DC Open to GND and DC Short to Pin 2	
Pin 2	RF Output	Pin 2 is DC Open to GND and DC Short to Pin 1	

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Specifications

Absolute Maximum Ratings

Parameter	Maximum Rating	Unit
DC Current	2	A
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C
RF Power Handling	4	W

Package Information

Parameter	Details	Rating
ESD	250 to < 500 Volts	HBM Class 1A
Dimensions	-	4.25 x 4.00 mm
Moisture Sensitivity Level	-	MSL 1

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Electrical Specifications

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
1 dBc Passband	Configuration A, Temp = 25°C	-	4.39	-	-	-	GHz
3 dBc Passband	Configuration A, Temp = 25°C	-	4.92	-	-	-	GHz
30 dBc Rejection Point	Configuration A, Temp = 25°C	-	5.45	-	-	-	GHz
Center Freq	Configuration A, Temp = 25°C	-	-	-	2.19	-	GHz
Passband Return Loss	Configuration A, Temp = 25°C	-	-	-	25	-	dB
Group Delay	Configuration A, Temp = 25°C	-	-	-	153	-	ps

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Typical Performance Plot









MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Performance Over Temperature



MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Mechanical Data

Outline Drawing

Download : Outline 2D Drawing

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVALS
A	Initial Release	11/18/25	AT





XXXXX	MFLP-#####GSM2
10928	MFLP-00042GSM2
10934	MFLP-00043GSM2
10935	MFLP-00044GSM2
10936	MFLP-00045GSM2
10937	MFLP-00046GSM2



Notes: (Unless otherwise specified)

1. Substrate Material Properties:
   CTE = 10 ppm/K
   Thermal Conductivity = 1.5 W/mK
   Thickness = 300um +/- 10um
2. Front to back registration to be ±10µm max.
3. Package length and width tolerance = +/- 20um
3. Finish: ENEPIG, 2.5µm Ni, 0.3µm Pd, 0.25µm Au.
4. Top and Bottom side metal thickness = 20um +/-4um
5. Top Side Solder Mask thickness = 5um
6. Shaded areas in this drawing are metalized

NOTES:		
DRAWN BY	DATE	
WV	3/27/25	
MB	11/3/25	

MATERIAL:

FINISH:

DO NOT SCALE DRAWING

Marki microwave www.markimicrowave.com

Circuit
Glass LPF

SIZE	CAGE CODE	DWG. NO.
A	0UC32	MFLP #####GSM2

SCALE 15/1 SHEET 1 OF 1

MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Footprint Image

Download : Footprint Drawing



MFLP-00045GSM2

Passive Glass 4.9 GHz Surface Mount Lowpass Filter

Evaluation Board - Outline Drawing



DISCLAIMER

MARKI MICROWAVE, LLC., (“MARKI”) PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES “AS IS” AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, LLC. All other trademarks used are the property of their respective owners.