Sales: 408-778-9952 | General: 408-778-4200 | Fax: 408-778-4300
Sales & Customer Support: sales@markimicrowave.com
Tech Support: support@markimicrowave.com


MFBP-00208PSM

Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter

DEVICE OVERVIEW

General Description

The MFBP-00208PSM passive MMIC surface mount bandpass filter is an ideal solution for small form factor, high rejection filtering. The MFBP-00208PSM features a 10.7 - 11.8 GHz 1 dBc passband and 3.2 dB center frequency insertion loss. Passive GaAs MMIC technology allows production of smaller filter constructions that replace larger form factor circuit board constructions. Tight fabrication tolerances allow for less unit-to-unit variation than traditional filter technologies. The MFBP-00208PSM is available as a 5 mm plastic QFN. Low unit to unit variation allows for accurate simulations using the provided S2P file taken from measured production units.



Download s-parameters here

Features

- Return Loss, 26 dB Typical
- Insertion Loss @ Fc, 3.2 dB Typical
- High Stop Band Suppression
- Wide Stop Band with Fast Roll-Off

Applications

N/A

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Green Status	Product Lifecycle	Export Classification
MFBP-00208PSM	Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter	PSM	RoHS REACH	Released	EAR99
EVB-MFBP-00208P	Evaluation Board, Passive GaAs 10.7 - 11.8 GHz MMIC Bandpass Filter	EVB	RoHS REACH	Released	EAR99

Rev: - | Copyright © 2026 Marki Microwave LLC.

MFBP-00208PSM

Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter

Table Of Contents

- **Device Overview**
  - General Description
  - Features
  - Applications
  - Functional Block Diagram
- **Port Configuration and Functions**
  - Port Diagram
  - Port Functions
- **Revision History**
- **Specifications**
  - Absolute Maximum Ratings
  - Package Information
  - Electrical Specifications
  - Typical Performance Plot
- **Mechanical Data**
  - Outline Drawing
- **Footprint Image**
- **Evaluation Board**
  - Evaluation Board Outline Drawing


Revision History

Revision Code	Revision Date	Comment
-	2026-10-07	Initial Release




Rev: - | Copyright © 2026 Marki Microwave LLC.

Port Configuration and Functions

Port Diagram



Port Functions

Port	Function	Description	DC Equivalent Circuit
Ground Paddle	Ground	PSM package ground path is provided through the ground paddle and should be connected to RF ground.	
Pin 20	Input/Output	Pin 20 is DC short to ground and open to Pin 5.	
Pin 5	Input/Output	Pin 5 is DC short to ground and open to Pin 20.	

Rev: - | Copyright © 2026 Marki Microwave LLC.

Specifications

Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Unit
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C
Pin 5 DC Current	400	mA
Pin 20 DC Current	400	mA

Package Information

Parameter	Details	Rating
ESD	1000 to < 2000 Volts	HBM Class 1C
Dimensions	-	5 x 5 mm

Rev: - | Copyright © 2026 Marki Microwave LLC.

Electrical Specifications

The electrical specifications apply at TA=+25°C in a 50Ω system. Typical data shown is for the filter in a PSM package with a sine wave input applied to Pin 5. Min and Max limits are guaranteed at TA=+25°C.


Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
1 dBc Passband	Temp = 25°C	10.71	11.77	-	-	-	GHz
3 dBc Passband	Temp = 25°C	10.54	11.95	-	-	-	GHz
30 dBc Rejection Point	Temp = 25°C	10.05	12.31	-	-	-	GHz
Center Freq	Temp = 25°C	-	-	-	11.23	-	GHz
Insertion Loss @ fc	Temp = 25°C	-	-	-	3.2	-	dB
Passband Return Loss	Temp = 25°C	-	-	-	26	-	dB
Group Delay	Temp = 25°C	-	-	-	966	-	ps

Rev: - | Copyright © 2026 Marki Microwave LLC.


MFBP-00208PSM


Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter


Typical Performance Plot











All measurements are de-embedded from the fixture with Automatic Fixture Removal (AFR).

Rev: - | Copyright © 2026 Marki Microwave LLC.

MFBP-00208PSM

Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter

Mechanical Data

Outline Drawing

Download : Outline 2D Drawing | Outline 3D Drawing | Outline 3D STP

All measurement are typical


PROJECTION INCH [MM]

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVALS
A	Initial Release	8/19/26	KM


XXXXX	MFBP-002##PSM
11525	MFBP-00208PSM
11528	MFBP-00205PSM
11529	MFBP-00206PSM
11558	MFBP-00210PSM

Pin #	Config A
1	N/C
2	N/C
3	N/C
4	N/C
5	RF
6	N/C
7	N/C
8	N/C
9	N/C
10	N/C
11	N/C
12	N/C
13	N/C
14	N/C
15	N/C
16	N/C
17	N/C
18	N/C
19	N/C
20	RF
21	N/C
22	N/C
23	N/C
24	N/C
25	N/C
26	N/C
27	N/C
28	N/C
29	N/C
30	N/C
31	N/C
32	N/C

5mm Plastic QFN



Bottom-up View:



Notes (unless otherwise specified):

1. Substrate material is LCP.
2. I/O Leads and Die Paddle are:
   0.008 - 0.05 µm Gold, over
   0.02 - 0.15 µm Palladium, over
   0.5 - 2.0 µm Nickel.
3. All unconnected pins should be connected to PCB RF ground.

Proprietary: This document was originated by and is the property of Marki Microwave. Unauthorized disclosure is prohibited.

NOTES:

MATERIAL:

FINISH: Note 2

DO NOT SCALE DRAWING

DRAWN BY	DATE
GM	5/29/26
OS, WV	8/18/26

Marki microwave www.markimicrowave.com

Outline
5mm QFN Filter

SIZE	CAGE CODE	DWG. NO.
A	0UC32	MFBP-002##PSM

SCALE 15/1 SHEET 1 OF 1


Rev: - | Copyright © 2026 Marki Microwave LLC.

MFBP-00208PSM

Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter

Footprint Image

Download : Footprint Drawing




Rev: - | Copyright © 2026 Marki Microwave LLC.

MFBP-00208PSM

Passive GaAs MMIC 10.7-11.8 GHz Bandpass Filter

Evaluation Board - Outline Drawing



Rev: - | Copyright © 2026 Marki Microwave LLC.

DISCLAIMER

MARKI MICROWAVE, LLC., (“MARKI”) PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES “AS IS” AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE, M wave logo, FastSwitch, and T3 MIXER are trademarks or registered trademarks of Marki Microwave, LLC. All other trademarks used are the property of their respective owners.

© 2026, Marki Microwave, LLC