


MMD-1030LCH

GaAs MMIC Doubler

DEVICE OVERVIEW

General Description

The MMD-1030L is a MMIC doubler fabricated with GaAs Schottky diodes. This part operates over a 5 to 15 GHz input frequency range or a doubled output frequency range of 10 to 30 GHz. It features excellent conversion loss, superior isolations, and harmonic suppressions across a broad bandwidth. Both the wire bondable die and connectorized units are available.




Features

- High Fundamental Rejection
- Low 2F Conversion Loss
- Low Input Drive

Applications

- High frequency synthesis
- LO signal chain

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Connectors	Green Status	Product Lifecycle	Export Classification
<u>MMD-1030LS</u>	GaAs MMIC Doubler	S	<u>Standard</u>	REACH RoHS	Released	EAR99
MMD-1030LCH	GaAs MMIC Doubler	CH	-	REACH RoHS	Released	EAR99

Table Of Contents

- **Device Overview**
 - General Description
 - Features
 - Applications
 - Functional Block Diagram
- **Port Configuration and Functions**
 - Port Diagram
 - Port Functions
- **Revision History**
- **Specifications**
 - Absolute Maximum Ratings
 - Package Information
 - Recommended Operating Conditions
 - Electrical Specifications
 - Typical Performance Plots
 - MMD-1030LS Typical Performance Plots
- **Die Mounting Recommendations**
 - Mounting and Bounding Recommendations
- **Mechanical Data**
 - Outline Drawing


Revision History

Revision Code	Revision Date	Comment
-	2022-12-01	Datasheet Initial Release




Port Configuration and Functions

Port Diagram

A top-down view of the MMD-1030L's CH package outline drawing is shown below.



Port Functions

Port	Function	Description	DC Equivalent Circuit
GND	Ground	CH package ground path is provided through the substrate and ground bond pads.	
Port 1	1F	Input 1x Frequency Port. Port 1 is DC open and AC matched to 50 Ohms from 5 to 15 GHz for the CH & S packages.	
Port 2	2F Output	2x Input Frequency output port. Port 2 is DC open and AC matched to 50 Ohms from 10 to 30 GHz for the CH & S packages.	

Specifications

Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. All Absolute Maximum Ratings are individual and should not be met in parallel. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Unit
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C
Power Handling, at any Port	25	dBm

Package Information

Parameter	Details	Rating
Dimensions	-	1.38 x 1.17 mm

Recommended Operating Conditions

The Recommended Operating Conditions indicate the limits, inside which the device should be operated, to guarantee the performance given in Electrical Specifications. Operating outside these limits may not necessarily cause damage to the device, but the performance may degrade outside the limits of the electrical specifications. For limits, above which damage may occur, see Absolute Maximum Ratings.

Parameter	Min	Nominal	Max	Unit
Operating Temperature	-55	25	100	°C
Input Power	5	7	15	dBm

Electrical Specifications









The electrical specifications apply at TA=+25°C in a 50Ω system. Typical data shown is for the connectorized S package doubler used in the forward direction with a +7 dBm sine wave input.

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
Conversion Loss	Second Harmonic Output	10	30	-	12.5	14	dB
Input Frequency Range	-	-	-	5	-	15	GHz
Input Power	-	-	-	5	7	15	dBm
Isolation, 1F ¹	Input=5-15 GHz Output=10-30 GHz	5	15	-	50	-	dB
Isolation, 3F ²	Input=5-10 GHz Output=15-30 GHz	15	30	-	58	-	dB
Isolation, 4F ³	Input=5-7.5 GHz Output=20-30 GHz	20	30	-	27	-	dB
Output Frequency Range	-	-	-	10	-	30	GHz
Suppression, 1F ⁴	Input=5-15 GHz Output=10-30 GHz	5	15	-	38	-	dBc
Suppression, 3F ⁵	Input=5-10 GHz Output=15-30 GHz	15	30	-	46	-	dBc
Suppression, 4F ⁶	Input=5-7.5 GHz Output=20-30 GHz	20	30	-	15	-	dBc

[1][2][3] Isolation is defined as the harmonic power relative to the 1F fundamental input power.









[4][5][6] Suppressions and isolations measured with an input source with >60dBc (relative to fundamental input) harmonic suppression. Suppression is defined as the harmonic power relative to the 2F doubled output power.

Typical Performance Plots



MMD-1030LS - Typical Performance Plots

Performance plots for the connectorized module are shown for measurements where directly probed measurements of the die are unavailable. Note that the following measurements include losses from connectors and microstrip traces.



Die Mounting Recommendations

Mounting and Bonding Recommendations

Marki MMICs should be attached directly to a ground plane with conductive epoxy. The ground plane electrical impedance should be as low as practically possible. This will prevent resonances and permit the best possible electrical performance. Datasheet performance is only guaranteed in an environment with a low electrical impedance ground.

Mounting - To epoxy the chip, apply a minimum amount of conductive epoxy to the mounting surface so that a thin epoxy fillet is observed around the perimeter of the chip. Cure epoxy according to manufacturer instructions.

Wire Bonding - Ball or wedge bond with 0.025 mm (1 mil) diameter pure gold wire. Thermosonic wirebonding with a nominal stage temperature of 150 °C and a ball bonding force of 40 to 50 grams or wedge bonding force of 18 to 22 grams is recommended. Use the minimum level of ultrasonic energy to achieve reliable wirebonds. Wirebonds should be started on the chip and terminated on the package or substrate. All bonds should be as short as possible <0.31 mm (12 mils).

Circuit Considerations – 50 Ω transmission lines should be used for all high frequency connections in and out of the chip. Wirebonds should be kept as short as possible, with multiple wirebonds recommended for higher frequency connections to reduce parasitic inductance. In circumstances where the chip more than .001" thinner than the substrate, a heat spreading spacer tab is optional to further reduce bondwire length and parasitic inductance.

Handling Precautions

General Handling


Chips should be handled with care using tweezers or a vacuum collet. Users should take precautions to protect chips from direct human contact that can deposit contaminants, like perspiration and skin oils on any of the chip's surfaces.

Static Sensitivity

GaAs MMIC devices are sensitive to ESD and should be handled, assembled, tested, and transported only in static protected environments.

Cleaning and Storage: Do not attempt to clean the chip with a liquid cleaning system or expose the bare chips to liquid. Once the ESD sensitive bags the chips are stored in are opened, chips should be stored in a dry nitrogen atmosphere.


Bonding Diagram




Mechanical Data

Outline Drawing

Download : [Outline 2D Drawing](#)



PROJECTION		REVISIONS			
INCH	MM	REV.	DESCRIPTION	DATE	APPROVALS
		A	ECN 24096 remove gel-pak info.	10/18/24	AT

<small>JUL 23 09 16 W 82 89 20 11 23 S/N 10 010 1/11 1 10 10 23 MMD-1030LCH</small>		NOTES: DRAWN BY: _____ DATE: _____ OG: _____ 11/1/2022		 www.markimicrowave.com	
MATERIAL: 210-06888-R25 FINISH: _____		SCALE: 40X		Outline MMIC Doubler DWG. NO. MMD-1030LCH	
PROPRIETARY: This document was originated by and is the property of Marki Microwave. Unauthorized disclosure is prohibited.		DO NOT SCALE DRAWING		SHEET 1 OF 1	

DISCLAIMER

MARKI MICROWAVE, LLC., ("MARKI") PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES "AS IS" AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, LLC. All other trademarks used are the property of their respective owners.

© 2022, Marki Microwave, LLC