Sales: 408-778-9952 | General: 408-778-4200 | Fax: 408-778-4300
Sales & Customer Support: sales@markimicrowave.com
Tech Support: support@markimicrowave.com

MMIQ-1865SUB

Passive GaAs MMIC IQ Mixer

DEVICE OVERVIEW

General Description

The MMIQ-1865S is a high linearity, passive MMIC IQ mixer. This is an ultra-broadband mixer spanning 18 to 65 GHz on the RF and LO ports with an IF from DC to 23 GHz. Up to 35 dB of image rejection is available due to the excellent phase and amplitude balance of its on-chip LO quadrature hybrid. Both wire bondable die and connectorized modules are available.



Features

N/A

Applications

- Single Sideband and Image Rejection Mixing
- IQ Modulation / Demodulation
- Vector Amplitude Modulation
- Band Shifting

Functional Block Diagram



Part Ordering Options

Part Number	Description	Package	Connectors	Green Status	Product Lifecycle	Export Classification
MMIQ-1865SUB	Passive GaAs MMIC IQ Mixer	UB	Standard	REACH RoHS	Released	EAR99

Rev: - | Copyright © 2019 Marki Microwave LLC.

Table Of Contents

- **Device Overview**
  - General Description
  - Features
  - Applications
  - Functional Block Diagram
- **Port Configuration and Functions**
  - Port Diagram
  - Port Functions
- **Revision History**
- **Specifications**
  - Absolute Maximum Ratings
  - Package Information
  - Recommended Operating Conditions
  - Sequencing Requirements
  - Electrical Specifications
  - Typical Performance Plots
- **Operation**
  - Application Circuit
  - Application Circuit Description
- **Mechanical Data**
  - Outline Drawing

Revision History

Revision Code	Revision Date	Comment
-	2019-10-01	Datasheet Initial Release

Rev: - | Copyright © 2019 Marki Microwave LLC.

Port Configuration and Functions

Port Diagram

A top-down view of the MMIQ-1865S's UB package outline drawing is shown below. The mixer may be operated as either a downconverter or an upconverter. Use of the RF or IF as the input or output port will depend on the application.



Function	Port Number	Connector Type
LO	1	1.85 mm Female
IF-Q	2	SMA Female
IF-I	3	SMA Female
RF	4	1.85 mm Female

Note: UB-Package Connectors are not removeable

Port Functions

Port	Function	Connector Type	Description	DC Equivalent Circuit
GND	Ground	-	UB package ground path is provided through the metal housing and outer coax conductor.	
Port 1	LO Input	1.85F	Port 1 is DC open and AC matched to 50Ω over the specified LO frequency range.	
Port 2	Q Input / Output	SMAF	Port 2 is diode coupled and AC matched to 50Ω over the specified Q port frequency range.	
Port 3	I Input / Output	SMAF	Port 3 is diode coupled and AC matched to 50Ω over the specified I port frequency range.	
Port 4	RF Input / Output	1.85F	Port 4 is DC open and AC matched to 50Ω over the specified RF frequency range.	

Rev: - | Copyright © 2019 Marki Microwave LLC.

Specifications

Absolute Maximum Ratings

The Absolute Maximum Ratings indicate limits beyond which damage may occur to the device. If these limits are exceeded, the device may be inoperable or have a reduced lifetime.

Parameter	Maximum Rating	Unit
Maximum Operating Temperature	100	°C
Maximum Storage Temperature	125	°C
Minimum Operating Temperature	-55	°C
Minimum Storage Temperature	-65	°C
Port 2 DC Current	23	mA
Port 3 DC Current	23	mA
Power Handling, at any Port	30	dBm

Package Information

Parameter	Details	Rating
ESD	250 to < 500 Volts	HBM Class 1A
Weight	Package name: UB	17g
Dimensions	-	16.26 x 16.26 mm

Recommended Operating Conditions

The Recommended Operating Conditions indicate the limits, inside which the device should be operated, to guarantee the performance given in Electrical Specifications. Operating outside these limits may not necessarily cause damage to the device, but the performance may degrade outside the limits of the electrical specifications. For limits, above which damage may occur, see Absolute Maximum Ratings.

Parameter	Min	Nominal	Max	Unit
Ambient Temperature	-55	25	100	°C
RF/IF Input Power	-	-	19	dBm
LO Input Power	23	25	27	dBm

Sequencing Requirements

There is no requirement to apply power to the ports in a specific order. However, it is recommended to provide a 50Ω termination to each port before applying power. This is a passive diode mixer that requires no DC bias.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Electrical Specifications

The electrical specifications apply at TA=+25°C in a 50Ω system. Typical data shown is for a down conversion application with a +21dBm sine wave LO input. Min and Max limits apply only to our connectorized units and are guaranteed at TA=+25°C. All bare die are 100% DC tested and visually inspected.

Parameter	Test Conditions	Minimum Frequency (GHz)	Maximum Frequency (GHz)	Min	Typ	Max	Unit
Conversion Loss [1]	RF/LO = 18 - 65 GHz I = 0.2 - 23 GHz	18	65	-	13	-	dB
Conversion Loss [2]	RF/LO = 18 - 65 GHz I = DC – 0.2 GHz	18	65	-	12	-	dB
Conversion Loss [3]	RF/LO = 18 - 65 GHz Q = 0.2 - 23 GHz	18	65	-	13	-	dB
Conversion Loss [4]	RF/LO = 18 - 65 GHz Q = DC -0.2 GHz	18	65	-	12	-	dB
IF Frequency Range	-	-	-	0	-	23	GHz
Image Rejection [5]	RF/LO = 18 - 65 GHz I+Q = DC – 0.2 GHz	18	65	-	35	-	dBc
Input 1 dB Gain Compression Point (P1dB), I	-	-	-	-	19	-	dBm
Input 1 dB Gain Compression Point (P1dB), Q	-	-	-	-	19	-	dBm
Input IP3 [6]	RF/LO = 18 - 65 GHz I = DC – 0.2 GHz	18	65	-	27	-	dBm
Isolation, LO to I	IF/LO = 18-65 GHz	18	65	-	45	-	dB
Isolation, LO to Q	IF/LO = 18-65 GHz	18	65	-	33	-	dB
Isolation, RF to I	RF/IF = 18-65 GHz	18	65	-	53	-	dB
Isolation, RF to Q	RF/IF = 18-65 GHz	18	65	-	53	-	dB
LO Frequency Range	-	-	-	18	-	65	GHz
LO-RF Isolation	RF/LO = 18-65 GHz	18	65	-	50	-	dB
Noise Figure [7]	RF/LO = 18 - 65 GHz I = DC – 0.2 GHz	18	65	-	12	-	dB
Noise Figure [8]	RF/LO = 18 - 65 GHz Q = DC – 0.2 GHz	18	65	-	13	-	dB
Q (Port 2) Frequency Range	-	-	-	0	-	23	GHz
RF Frequency Range	-	-	-	18	-	65	GHz

[1][2][3][4] Measured as an I/Q down converter. (i.e., I and Q powers are not combined)
[5] Image Rejection and Single sideband performance plots are defined by the upper sideband (USB) or lower sideband (LSB) with respect to the LO signal. Plots are defined by which sideband is selected by the external IF quadrature hybrid.
[6] Typical IIP3 measured with I and Q ports combined with an external quadrature hybrid coupler.
[7][8] Mixer Noise Figure typically measures within 0.5 dB of conversion loss for IF frequencies greater than 5 MHz.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Typical Performance Plots

Due to limited available LO power, all performance plots are measured with a +21dBm LO drive and in most cases bandlimited to 45 GHz. Data is not representative of the performance of a properly operated unit. Linear performance at high frequency and high LO power is similar to MMIQ-1865H. See MMIQ-1865H datasheet for expected linear performance.

I output means that the IF output signal is measured at the I port of the mixer and the Q port is loaded. Q output means the IF output signal is measured at the Q port of the mixer while the I port is loaded.













Rev: - | Copyright © 2019 Marki Microwave LLC.

IF Return Loss (dB)



LO to IF Isolation (dB)



RF to IF Isolation (dB)



USB I+Q Downconversion Loss vs. LO Power (dB)[4]



USB I+Q Image Rejection vs. LO Power (dB)[4]



LSB I+Q Downconversion Loss vs. LO Power (dB)[4]



LSB I+Q Image Rejection vs. LO Power (dB)[4]



USB I+Q Upconversion Loss vs. LO Power (dB)[4]



Rev: - | Copyright © 2019 Marki Microwave LLC.

USB I+Q Sideband Suppression vs. LO Power (dB)[4]



LSB I+Q Upconversion Loss vs. LO Power (dB)[4]



LSB I+Q Sideband Suppression vs. LO Power (dB)[4]



Input IP3 (dBm)[4]



Output IP3 (dBm)[4]



Even LO Harmonic to RF Isolation (dB)



Odd LO Harmonic to RF Isolation (dB)



Spur Suppression, Upconversion, IF=91 MHz, LSLO, 1LOx2IF (dBc)[7]



Rev: - | Copyright © 2019 Marki Microwave LLC.

Spur Suppression, Upconversion, IF=91 MHz, LSLO, 1LOx3IF (dBc)[7]



Spur Suppression, Upconversion, IF=91 MHz, LSLO, 1LOx4IF (dBc)[7]



Spur Suppression, Upconversion, IF=91 MHz, LSLO, 1LOx5IF (dBc)[7]



Spur Suppression, Downconversion, IF=91 MHz, LSLO, 2LOx2RF (dBc)[7]



Spur Suppression, Downconversion, IF=91 MHz, LSLO, 3LOx3RF (dBc)[7]



Spur Suppression, Downconversion, IF=91 MHz, LSLO, 4LOx4RF (dBc)[7]



Spur Suppression, Downconversion, IF=91 MHz, LSLO, 5LOx5RF (dBc)[7]



Spur Suppression, Downconversion, IF=14 GHz, LSLO, 2LOx-1RF (dBc)[7]



Rev: - | Copyright © 2019 Marki Microwave LLC.

Spur Suppression, Downconversion, IF=14 GHz, LSLO, 3LOx-2RF (dBc)[7]



Spur Suppression, Downconversion, IF=14 GHz, LSLO, 4LOx-3RF (dBc)[7]



Spur Suppression, Downconversion, IF=14 GHz, LSLO, 5LOx-4RF (dBc)[7]



Spur Suppression, Downconversion, IF=7 GHz, HSLO, -2LOx3RF (dBc)[7]



Spur Suppression, Downconversion, IF=7 GHz, LSLO, -3LOx4RF (dBc)[7]



Vector Modulator Insertion Loss (dB)[6]



Vector Modulator Group Delay (ps)[6]



Rev: - | Copyright © 2019 Marki Microwave LLC.

Application Circuit



IQ Mixer



Internal Structure

Rev: - | Copyright © 2019 Marki Microwave LLC.

Application Circuit Description

Detailed Description

MMIQ-1865 belongs to Marki Microwave's MMIQ family of mixers. The MMIQ product line consists of passive GaAs MMIC mixers designed and fabricated with GaAs Schottky diodes. MMIQ mixers offer excellent amplitude and phase balance from the due to its on-chip LO quadrature hybrid. Up to 35dB of image rejection (i.e., single sideband suppression) can be obtained by using the MMIQ-1865 as an image rejection or single sideband mixer. The MMIQ-1865L and MMIQ-1865H are the sister mixers of the MMIQ-1865S. The MMIQ-1865L and MMIQ-1865H both require a lower LO drive to operate the mixer. In exchange, both display lower linearity (i.e., lower IIP3, P1dB, Spurious Suppression) than the MMIQ-1865S. Marki S, H, and L diodes correspond to different diode forward turn on voltages.

Support for the K, through V bands are offered by the ultra-broadband performance of the mixer's RF and LO ports (ports 1 and 4). Direct baseband to V band frequency conversions are available by using this mixer as an up-converter. Traditional use of this mixer to do image reject or single sideband mixing is available with an external IF quadrature hybrid. The MMIQ-1865 is also suitable for use as a Vector Modulator through DC bias of the I and Q ports (ports 2 and 3).

Port 1, the LO port, and port 4, the RF port, support an 18-65GHz signal. Ports 2 and 3, the I and Q ports, support a DC-23GHz signal. A signal may be input into any port of the mixer which supports that signal's frequency. This is the basis of using the mixer as a band shifter.

For a given LO power within the recommended operating range, the RF (in the case of a down conversion) or IF (in the case of an up conversion) input power should be below the input 1dB compression point to avoid signal distortion. The input 1dB compression point will vary across the mixer's operating bandwidth and with LO input power. Careful characterization is required for optimal performance for each application. There is no minimum small signal input power required for operation. Excessive RF/IF input power increases non-desired spurious output power and degrades the fundamental conversion loss. Excessive LO input power can also cause this effect. The table below describes how to use an IQ mixer and quad hybrid to select a single sideband.

Up Conversion		
Hybrid Port	Mixer Port	Sideband Selected
0	I	Lower Sideband
90	Q	
90	I	Upper Sideband
0	Q	
Down Conversion		
Hybrid Port	Mixer Port	Sideband Selected
0	I	Upper Sideband
90	Q	
90	I	Lower Sideband
0	Q	

Rev: - | Copyright © 2019 Marki Microwave LLC.

Down-Converter



A down converter is a mixer application which takes a high frequency small signal RF input, and a high frequency large signal LO input and mixes the signals together to produce a low frequency IF output. The fundamental 1RFx1LO outputs present at the IF port are the f_{LO-RF} and f_{LO+RF} tones. The desired output in a down conversion is typically the f_{LO-RF} term. An image frequency at $f_{Image}=f_{2LO-RF}$ will also down convert to the f_{LO-RF} frequency. The above illustration shows the relative location of the image frequency for a highside LO, or the frequency plan for which $f_{LO} > f_{RF}$.

To use the IQ mixer as a down converter, input a high frequency small signal RF input into port 4, a high frequency large signal LO input into port 1, and pull the low frequency IF output from ports 2 and 3. Ports 2 and 3 will output the IF signals I and Q. I and Q IF outputs will be at the same frequency but 90° out of phase (i.e., I and Q are in quadrature). If only a single IF output is desired, terminate either the I or Q ports with a wideband 50Ω load.

This is the input scheme was used to take I/Q down-conversion data found in the Typical Performance Plots.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Image Reject Down-Converter



An image reject mixer is a mixer which rejects the down converted image frequency from the IF output. Image reject mixers are constructed using an external quadrature hybrid attached to the I and Q (i.e., IF) output ports. Using the external IF quadrature hybrid, one can select whether the upper sideband or lower sideband signal is suppressed with respect to the LO signal.

To use the IQ mixer as an image reject mixer, input the high frequency small signal RF into port 4 and a high frequency large signal LO input into port 1. Take the combined I+Q down converted signal through the IF quadrature hybrid. Select the upper sideband (i.e., suppress the lower sideband) by connecting the I port to the 0° port of the IF quadrature hybrid and attach the Q port to the 90° port of the IF quadrature hybrid. Select the lower sideband (i.e., suppress the upper sideband) by attaching the I port to the 90° port of the IF quadrature hybrid and attach the Q port to the 0° port of the IF quadrature hybrid.

This is the input scheme was used to take image rejection down-conversion data found in the Typical Performance Plots.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Up-Converter



An up converter is a mixer application which takes a low frequency small signal IF input, and a high frequency large signal LO input and mixes the signal together to produce a high frequency RF output. The fundamental 1IFx1LO outputs present at the RF port are the f_{LO-IF} and f_{LO+RF} tones. An up conversion can select either the f_{LO-IF} or the f_{LO+IF} tones. The above illustration shows both up converted sidebands with either an I or Q port input signal.

To use the IQ mixer as an up converter, input a low frequency small signal IF input into port 2 or 3, a high frequency large signal LO input into port 1, and pull the high frequency RF output from port 4. Input into the Q port will result in a up converted signal that is 90° out of phase with the up converted I port input signal. If only a single IF input is desired, terminate either the I or Q ports with a wideband 50Ω load.

This is the input scheme used to take I/Q up-conversion data found inTypical Performance.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Single Sideband Up-Converter





A single sideband mixer is a mixer which suppresses the up converted image frequency from the RF output. Single sideband mixers are constructed using an external quadrature hybrid attached to the I and Q (i.e., IF) input ports. Using an external IF quadrature hybrid, one can select whether the upper sideband or the lower sideband signal is suppressed with respect to the LO signal.

To use the IQ mixer as a single sideband mixer, input the low frequency small signal I+Q IF signal into the IF quadrature hybrid. The IF quadrature hybrid is attached to the I and Q ports of the IQ mixer. Input the high frequency large signal LO input into port 1 and take the up converted high frequency RF signal from port 4. Select the upper sideband (i.e., suppress the lower sideband) by attaching the I port to the 90° port of the IF quadrature hybrid and attach the Q port to the 0° port of the IF quadrature hybrid. Select the lower sideband (i.e., suppress the upper sideband) by attaching the I port to the 0° port of the IF quadrature hybrid and attach the Q port to the 90° port of the IF quadrature hybrid.

This is the input scheme used to take single sideband up-conversion data found inTypical Performance.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Band Shifter





A band shifter is an unusual application for a mixer. Band shifters take an IF signal and shift it to a different band, generally to either avoid interference or for rebroadcast at a different frequency. For cases in which the desired band shift cannot be employed by using a standard up or down conversion scheme, an exotic input scheme is required.

A passive diode mixer is reciprocal on all ports. Port 4, the RF port, supports a 18-65GHz signal. Port 1, the LO port, supports a 18-65GHz signal. Ports 2 and 3, the IF ports, support a DC-23GHz signal. 2 signals input into any combination of the 3 ports, RF, LO, or IF, will result in an output signal at the 3rd port. In addition, an output signal will be present at both input ports. By using the IF port, as a large signal input port, low frequency LO applications can be supported.

The diagram above shows an IQ mixer being used as a band shifter. Using an IQ mixer as a band shifter allows for sideband suppression. This is identical to using the IQ mixer as a single sideband up converter. However, the large signal input port is now 2+3 versus port 1. Selection of the output tone is done through the orientation of the LO quadrature hybrid.

To use the mixer as a single sideband band shifter, input a low frequency large signal LO into the external LO quadrature hybrid. Input the high frequency small signal IF signal into port 1 and take the high frequency RF output from port 4. Select the upper sideband (i.e., suppress the lower sideband) by attaching the I port to the 90° port of the IF quadrature hybrid and attach the Q port to the 0° port of the LO quadrature hybrid. Select the lower sideband (i.e., suppress the upper sideband) by attaching the I port to the 0° port of the LO quadrature hybrid and attach the Q port to the 90° port of the LO quadrature hybrid.

Using this input scheme requires careful accounting of which input signal is injecting which port. Injecting a signal into any port which does not support the correct band will lead to a degraded or no output response. Abide by the maximum DC current input into the I and Q ports of the mixer or otherwise irreversible damage to the mixer will occur.

The limiting factor in use of the mixer as an image reject band shifter is in the bandwidth of the external LO quadrature hybrid and bandwidth of the I and Q ports.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Vector Modulator



A vector modulator is a device that can modulate an input signal's amplitude and phase. Similar to using a double balanced mixer as a phase modulator or phase shifter, an IQ mixer can be used as a vector modulator. An IQ mixer can be used as a vector modulator by inputting DC current into both the I and Q ports.

Injecting DC current into both the I and Q ports forward biases both mixer cores and causes them to be shorted. This connects the RF and LO baluns allowing the input signal to pass from balun to balun without a frequency conversion. Modulating the DC current into either or both I and Q mixers causes both the phase and amplitude to modulate based on the polarity of the input current and the magnitude of the input current. Modulating only the I or Q mixers causes the device to behave as a biphase modulator (i.e., the device can only swing the phase from +90° to -90°).

To use the IQ mixer as a vector modulator, supply a DC current sufficient to turn on the mixer through both the I and Q ports. Current limiting the DC source to the maximum DC current value found inAbsolute Maximum Ratings is recommended to prevent irreversible damage to the vector modulator. The typical DC current required to turn on the vector modulator is <30mA.

It is recommended to sequence the vector modulator by slowly increasing the DC bias until the vector modulator is operating at the user desired condition.

Near the band edges of the vector modulator, more current than is typical for mid-band operation may be necessary to achieve the same amplitude and phase shift. This is due to the on chip LO quadrature hybrid operating near its band edge.

Rev: - | Copyright © 2019 Marki Microwave LLC.

Mechanical Data

Outline Drawing

Download : Outline 2D Drawing | Outline 3D Drawing | Outline 3D STP



Function	Port Number	Connector Type
LO	1	1.85 mm Female
IF-Q	2	SMA Female
IF-I	3	SMA Female
RF	4	1.85 mm Female
Note: UB-Package Connectors are not removeable		

Rev: - | Copyright © 2019 Marki Microwave LLC.

DISCLAIMER

MARKI MICROWAVE, LLC., (“MARKI”) PROVIDES TECHNICAL SPECIFICATIONS AND DATA (INCLUDING DATASHEETS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER INFORMATION AND RESOURCES “AS IS” AND WITH ALL FAULTS. MARKI DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

These resources are intended for developers skilled in the art designing with Marki products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards and other requirements. Marki makes no guarantee regarding the suitability of its products for any particular purpose, nor does Marki assume any liability whatsoever arising out of your use or application of any Marki product.

Marki grants you permission to use these resources only for development of an application that uses Marki products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Marki intellectual property or to any third-party intellectual property. Marki reserves the right to make changes to the product(s) or information contained herein without notice.

MARKI MICROWAVE and T3 MIXER are trademarks or registered trademarks of Marki Microwave, LLC. All other trademarks used are the property of their respective owners.

© 2019, Marki Microwave, LLC